



# kramer

## SC42DHU-3

HighSecLabs Secure 4-Port 4K30 UHD  
DVI-I to HDMI KVM Combiner with fUSB

| DVI | HDMI | C-KVM



SC42DHU-3 is a secure 4-port 4K30 UHD DVI-I to HDMI KVM combiner. It enables users to share peripherals – keyboard, video, mouse, audio and USB – between two different security-level networks/computers while isolating all hosts and protecting against data leakage and malicious attacks through shared peripherals. It also enables assigning a USB port to a specific computer while switching other peripherals, such as when a USB smart card reader must remain mapped to a certain computer. Advanced multiviewer and scaling capabilities enable increased productivity in environments that require viewing and interacting with many computers simultaneously. SC42DHU-3 provides the highest possible isolation between connected computers and is designed to meet the security requirements of government agencies, military, financial institutions, and similar security-sensitive customers

## FEATURES

**Secure by Design** - Meets the security requirements demanded by government agencies, military, financial institutions, and similar security-sensitive customers

**4K30 UHD Resolution** - Supports resolutions up to 3840×2160 @30Hz

**Work Freely Without Compromising Security** - Control classified and non-classified computers without compromising security

**Prevent Information Leaks** - Block peripheral exploits, information leaks, eavesdropping, signal transmission, computer malware, hardware and firmware tampering

**Filter USB Peripherals** - Allow or block specific USB devices based on VID/PID characteristics

**Biometric/Smart-Card Reader Support** - Connect a smartcard/biometric reader to the secure port to support user authentication across multiple isolated computers

**Keyboard Lock Indication** - Caps Lock, Num Lock, and Scroll Lock indication on front panel

**Native Touch Screen Support** - Interact with all connected computers using touch screen gestures, with no need for additional drivers or software. Compatible with standard Microsoft™ Digitizer driver-based touch screens without internal hubs

**Flexible Display Layouts** - Resize source scaling and aspect ratio to create tile, scale and custom display layouts. Supports duplication and extended display view modes



# kramer

## TECHNICAL SPECIFICATIONS

---

**CONSOLE PORTS:** 2 HDMI connectors, 2 USB-A connectors for keyboard and mouse, 1 USB-A connector for USB devices, 2 DIN-5 connectors for PS/2 keyboard and mouse, 1 3.5mm mini jack for unbalanced stereo audio, 1 RJ45 connector for control (RDC)

**MAX OUTPUT RESOLUTION:** 4K30 UHD (3840X2160 @30Hz)

**COMPUTER PORTS:** 4 DVI-I (single-link/dual-link) connectors, 4 USB-B connectors for keyboard and mouse, 4 USB-B connectors for USB devices, 4 3.5mm mini jacks for unbalanced stereo audio

**MAX INPUT RESOLUTION:** 1920x1200

**POWER REQUIREMENTS:** 35W max

**AC INPUT:** 100V to 240V AC

**POWER TYPE:** External

**OPERATING TEMPERATURE:** 0° to +40°C (32° to 104°F)

**STORAGE TEMPERATURE:** -20° to +60°C (-4° to 140°F)

**HUMIDITY:** 0% to 80%, RH non-condensing

**SUPPORTED OS:** Windows, Linux, Mac

**PRODUCT CERTIFICATION:** CE, RCM, FCC class B, VCCI, TUV US, TUV Canada

**PRODUCT LIFE-CYCLE:** 10 years

**Product Dimensions** 32.00cm x 13.00cm x 5.20cm (12.60" x 5.12" x 2.05" ) W, D, H

**Product Weight** 1.5kg (3.4lbs) approx

**Shipping Dimensions** 45.00cm x 20.00cm x 12.00cm (17.72" x 7.87" x 4.72" ) W, D, H

**Shipping Weight** 2.7kg (6.0lbs) approx

